



Traceable® Extra-Extra-Loud Timer



Perfect for high sound zones—indoors and out

User-friendly timer features include countdown, stopwatch, time-out, and time-of-day clock. May be heard in the noisiest plant or lab. One hundred decibel alarm penetrates high noise areas clearly. A breakthrough for easily hearing a countdown alarm in high ambient noise conditions.



Set two separate channels

Giant display permits viewing anywhere. Massive display is 19 mm-high. Micro computer chip permits setting two separate channels. Set any time from 99 hours, 59 minutes, 59 seconds to 1 second. When zero is reached the timer starts counting up to show time elapsed since alarming.

One-hundred-decibel screamer

Both channels may be used simultaneously as countdown, count-up (stopwatch), or in any combination of count-up/countdown. Memories return the display to the previously programmed countdown time at the touch of a button. The extra-extra-loud, one-hundred-decibel alarm sounds for 1 minute or may be silenced manually. Finger-sized keys make it easy to set times and change channels. Quartz-crystal accuracy is 0.01%. To assure accuracy an individually serial-numbered Traceable® Certificate is provided from an ISO 17025 calibration laboratory accredited by A2LA (A2LA, DSM and SAC calibration certificates are all mutually recognised). It indicates traceability to standards provided by NIST (National Institute of Standards and Technology). It provides the accurate timing assurance demanded by government regulations and ISO 9000 requirements. Solid-state components tolerate rough handling. Magnetic back allows timer to be placed on any metal surface. It also has a flip-open easel for standing. Supplied with two-year batteries. Size is 102 x 64 x 12.7 mm. Weight is 142 g.



Traceable® Jumbo Timer



Allows simultaneous programming of two different activities from 24 hours to 1 second. Resolution is 1 second; accuracy is 0.01%. Each channel has a distinct electronic alarm and display indicator when zero is reached. The alarm may be turned off or it is silenced automatically after 1 minute.

For repetitive timing, a memory recalls the last countdown time set. A second display mode shows time-of-day and a stopwatch (for count-up timing). Jumbo, 25.4 mm-high LCD digits may be read from 9 m.

Use it flat, in the sit up position, or wall-mount with the bracket supplied. Size is 95 x 140 x 12.7 mm. Weight is 142 g. Supplied with AAA battery providing 2 years of normal usage. To assure accuracy an individually serial-numbered Traceable® Certificate is provided from an ISO 17025 calibration laboratory accredited by A2LA (A2LA, DSM and SAC calibration certificates are all mutually recognised). It indicates traceability to standards provided by NIST (National Institute of Standards and Technology).

Description	Cat. No.	Description	Cat. No.
Fisher Scientific Traceable® Extra-Extra-Loud Timer	15-077-64	Fisher Scientific Traceable® Jumbo Timer (Black)	06-662-47
		Fisher Scientific Traceable® Jumbo Timer (White)	06-662-48