


# FC 203B/FC 204 Fraction Collectors

## Time, drop or peak collection to suit virtually any fraction collection application

The FC 203B and FC 204 Fraction Collectors are ideal instruments to integrate with any HPLC system. Capable of collecting into a variety of vessels these fraction collectors can also be used in a stand-alone operation using time, drop or peak based collection.



### Features & Benefits

- ▶ Choose the compact FC 203B for lower capacity or the FC 204 for large volumes and capacities
- ▶ Accepts a wide variety of collection vessels, including microplates, vials, and tubes
- ▶ In peak mode, the collector monitors a detector signal and identifies peaks using either an adaptive slope algorithm or a specified millivolt threshold
- ▶ Up to ten programmable time windows can be added for collecting specified samples while discarding the column void volume, peaks of no interest and equilibration volumes
- ▶ Operate as a stand-alone instrument with incorporated keypad or control through TRILUTION® LC Software
- ▶ 3-way diverter valve prevents contamination of collected fractions (standard on the FC 204, optional on the FC 203B)
- ▶ Contact closure inputs are available to remotely start, advance or stop fraction collection—compatible with most HPLC systems
- ▶ Multi-column adapters for collecting up to 18 separate channels (9 on the FC 203B)
- ▶ Compact size; fits in most fume hoods

# FC 203B/FC 204 Fraction Collectors

## Applications

- Fraction collection to microplates or tubes for compound purification

FC 203B/FC 204 Fraction Collectors	
<b>3-way Valves</b>	FC 203B/204: 3-port, PTFE, 67 $\mu$ L internal volume, 3.5 $\mu$ L dead volume from the common port to the normally closed port, up to 20 mL/min with a large-bore needle FC 204: 3-port, PTFE, 114 $\mu$ L internal volume, 10 $\mu$ L dead volume from common port to normally closed port, up to 200 mL/min with a large-bore needle Operating pressure: 30 psi on the NO and NC port, 60 psi on the COMM port Valve switching speed < 20 msec
<b>Detector Input</b>	$\pm$ 100 mV full scale
<b>Drop Counting</b>	Up to 9,999 drops per fraction Maximum rate: 20 drops/sec
<b>Operating Modes</b>	Drop, Manual, Peak + Drop, Peak + Time, Time
<b>Peak Detection</b>	Adaptive slope algorithm that applies user-specified parameters to accommodate drifting baselines, negative and asymmetrical peaks or absolute threshold level that collects all peaks above specified mV value Peak parameters: peak height or level, in mV; peak width at half-height, in min Minimum peak height for fractionation: 0.1 mV full scale Detector-collector delay: 0.01 min increments
<b>Multiple-cycle Operation</b>	Repetitive collection of each sample into same set of tubes or collection of each sample into different sets of tubes
<b>Multiple-column Collection</b>	Simultaneous collection from up to 9 (FC 203B) or up to 18 (FC 204) columns with installation of optional multiple column adapter(s)
<b>Maximum Fractions</b>	FC 203B: 128 – 12 x 75 mm tubes using a Code 14 Rack FC 204: Up to 768 using a Code 17 rack with eight 96-well, 2 mL Whatman/Polyfiltronics microplates
<b>Maximum Collection Volume/Tube</b>	FC 203B: 20 mL (28 x 60 mm) scintillation using a Code 24 rack FC 204: 32 mL (18 x 180 mm) tubes using a Code 22 rack
<b>Rack Capacity</b>	FC 203B: one rack FC 204: one Code 16 or Code 16D, Code 17 or up to four Code 20-series racks (all racks must be the same)
<b>Front Panel Display</b>	HELP, YES, NO, 0-9 numeric hard keys and four soft keys and 2-line, 24-character display on backlit LCD
<b>Software Control</b>	Stand-alone instrument controlled using an incorporated keypad or through TRILUTION® LC Software
<b>Safety Approvals/ EMC Compliance</b>	Meets applicable safety and EMC certification standards; UL and CE certified
<b>Power Requirements</b>	Frequency: 50 – 60 Hz Voltage: 100 – 120 or 220 – 240V; mains voltage fluctuations not to exceed $\pm$ 10% of the nominal voltage Current rating: 0.5A for 100 – 120V, or 0.25A for 220 – 240V
<b>Dimensions (w x d x h)</b>	FC 203B: 32.4 x 29.2 x 26.7 cm (12.8 x 11.5 x 10.5 in) FC 204: 47.9 x 46.4 x 33 cm (18.9 x 18.3 x 13 in)
<b>Weight</b>	FC 203B: 5 kg (11 lbs.) FC 204: 10.9 kg (24 lbs.)

### Product #s:

- 171011 (FC 203B)
- 171011DV (FC 203B, 3-way valve)
- 171041 (FC 204)
- 171043 (FC 204, prep valve)



**Gilson, Inc. World Headquarters** | 3000 Parmenter Street | P.O. Box 620027 | Middleton, WI 53562-0027, USA | Tel: 608-836-1551 or 800-445-7661 | Fax: 608-831-4451

**Gilson S.A.S.** | 19, avenue des Entrepreneurs | BP 145, F-95400 VILLIERS LE BEL, FRANCE

**www.gilson.com** | sales@gilson.com | service@gilson.com | training@gilson.com

