

- Accurate temperature control from 0°C to 60°C
- Powerful compressor, maintains 0°C
- Stainless-steel internal chamber
- Internal power inlet for shakers, mixers, etc.
- 💳 Sized for floor standing use or on bench-tops (less than 32" tall)





Stainless-steel chamber with internal outlet & light

The myTemp 65HC Incubator is designed to provide accurate and uniform temperature control from 0 to 60°C. The broad temperature range of the instrument expands the use of this incubator to both heating and cooling applications.

A large, digital display allows for visualization of the chamber temperature and the remaining incubation time, while an internal light is included for improved visualization of the chamber. In addition, a built in, internal outlet can be used to provide power to small instruments, such as shakers, rockers, etc.

With forced air technology and stainless steel inner construction, uniform heat transfer is ensured throughout the internal chamber. When set for sub-ambient temperatures, the powerful compressor is activated, quickly cooling the chamber to the desired temperature.

With an exterior height of 39 inches (100cm), the incubator is designed to be floor-standing, yet is also compact enough for bench-use. (Not recommended for use on benchtops taller than 32"/81cm). The instrument is supplied with two, adjustable height shelves, while additional shelves can also be purchased separately (item: H2265-SH).

Technical Data

Temp. Range: 0°C to 60°C (RT-25°C to 60°C) Temp. Accuracy: 0.5°C (at 37°C)

all Hill Harin

Temp. Uniformity: +/- 1.0.°C (at 37°C) 0.1°C

Temp. Increments:

Dimensions:

Exterior: (WxDxH) 21.25 x 21 x 39.35 in. 54 x 53.34 x 99.85 cm 15.75 x 12.75 x 19.75 in. Interior: 40 x 32.4 x 50.2 cm

Capacity: 65L or 2.3 cubic feet 117 lbs (53kg) Weight: 120V, 60Hz or 230V, 50Hz* (385W)

Electrical:

Warranty: 2 years

Ordering Information:

H2265-HC* MyTemp™ 65 Heating and Cooling

Incubator, includes two stainless steel shelves

H2265-SH Extra shelf, stainless steel

* 115V with US plug. For 230V (EU plug), please add (-E)



PO Box 709 Edison, NJ 08818 Fax: 732-313-7007 Phone: 908-769-5555 Web: www.BenchmarkScientific.com Email: Info@BenchmarkScientific.com